

LinkSys PAP2 Configuration to use SIP Micro's SIP VoIP Account

Line 1 page

LINKSYS
A Division of Cisco Systems, Inc.

Firmware Version: 3.1.8(L3)

Phone Adaptor with 2 Ports for Voice Over IP **PAP2**

Voice

Info System SIP Regional **Line 1** Line 2 User 1 User 2

Basic View (switch to advanced view) [User Login](#)

SIP Settings

Line Enable:

SP Port:

Proxy and Registration

Proxy: Register:

Make Call Without Reg: Register Expires:

Ans Call Without Reg:

Subscriber Information

Display Name: User ID:

Password: Use Auth ID:

Auth ID:

Supplementary Service Subscription

Call Waiting Serv: <input type="text" value="yes"/>	Block CID Serv: <input type="text" value="yes"/>
Block ANC Serv: <input type="text" value="yes"/>	Dist Ring Serv: <input type="text" value="yes"/>
Cfwd All Serv: <input type="text" value="yes"/>	Cfwd Busy Serv: <input type="text" value="yes"/>
Cfwd No Ans Serv: <input type="text" value="yes"/>	Cfwd Sid Serv: <input type="text" value="yes"/>
Cfwd Last Serv: <input type="text" value="yes"/>	Block Last Serv: <input type="text" value="yes"/>
Accept Last Serv: <input type="text" value="yes"/>	DND Serv: <input type="text" value="yes"/>
CID Serv: <input type="text" value="yes"/>	CWCD Serv: <input type="text" value="yes"/>
Call Return Serv: <input type="text" value="yes"/>	Call Boot Serv: <input type="text" value="yes"/>
Three Way Call Serv: <input type="text" value="yes"/>	Three Way Conf Serv: <input type="text" value="yes"/>
Attn Transfer Serv: <input type="text" value="yes"/>	Unattn Transfer Serv: <input type="text" value="yes"/>
MVM Serv: <input type="text" value="yes"/>	VMM Serv: <input type="text" value="yes"/>

Audio Configuration

Preferred Codec: Silence Supp Enable:

Use Pref Codec Only: FAX CED Detect Enable:

DTMF Tx Method:

CISCO SYSTEMS

System page

LINKSYS
A Division of Cisco Systems, Inc.

Firmware Version: 3.1.8(LS)

Voice Phone Adapter with 2 Ports for Voice-Over-IP PAP2

Info **System** SIP Regional Line 1 Line 2 User 1 User 2

Basic View (switch to advanced view) [User Login](#)

System Configuration

Internet Connection Type

Optional Network Configuration

Enable Web Server:	yes ▾	User Password:	<input type="text"/>
DHCP:	yes ▾	NetMask:	<input type="text"/>
Static IP:	<input type="text"/>	Gateway:	<input type="text"/>
HostName:	<input type="text"/>	Domain:	<input type="text"/>
Primary DNS:	<input type="text"/>	Secondary DNS:	<input type="text"/>
DNS Query Mode:	Parallel ▾	Syslog Server:	<input type="text"/>
Debug Server:	<input type="text"/>	Debug Level:	0 ▾

CISCO SYSTEMS