

WellTech FXS Configuration to use SiP Micro's SIP VoIP Account

SIP Information	
Run Mode:	<input type="radio"/> Peer-2-Peer <input checked="" type="radio"/> Proxy <input type="radio"/> Gateway
Primary Proxy IP Address:	<input style="color: red;" type="text" value="SIP Proxy DNS name or IP"/>
Primary Proxy port:	<input type="text" value="5060"/>
Secondary Proxy IP Address:	<input type="text" value="null"/>
Secondary Proxy port:	<input type="text" value="5060"/>
Outbound Proxy:	<input style="color: red;" type="text" value="SIP Proxy DNS name or IP"/>
Outbound Proxy port:	<input type="text" value="5060"/>
Prefix String:	<input type="text" value="null"/>
Line1 Number:	<input style="color: red;" type="text" value="NUMBER/ANI"/>
Line1 Account:	<input style="color: red;" type="text" value="NUMBER/ANI"/>
Line1 Password:	<input style="color: red;" type="text" value="NUMBER/ANI"/>
Line2 Number:	<input type="text"/>
Line2 Account:	<input type="text"/>
Line2 Password:	<input type="text"/>
SIP port:	<input type="text" value="5060"/>
RTP Port:	<input type="text" value="16384"/>
Expire:	<input type="text" value="60"/>
<input type="button" value="OK"/>	

System Configuration	
Keypad DTMF Type:	<input type="radio"/> In-Band <input checked="" type="radio"/> RFC2833 <input type="radio"/> INFO
RFC2833 Payload Type:	<input type="text" value="96"/>
FAX Payload Type:	<input type="text" value="101"/>
Inter Digit Time:	<input type="text" value="3"/>
CallerID Type:	<input checked="" type="radio"/> disable <input type="radio"/> FSK(BELLCORE) <input type="radio"/> DTMF
Busy Forward:	<input checked="" type="radio"/> ON <input type="radio"/> OFF
End of Dial Digit:	<input type="radio"/> NONE <input type="radio"/> * <input checked="" type="radio"/> #
<input type="button" value="OK"/>	

Voice Setting					
Codec Priority	1st G.723.1 ▼	2nd G.729 ▼	3rd G.729a ▼	4th G.711mu-Law ▼	5th G.711A-Law ▼
Frame Size	G.723.1 30ms ▼	G.729 20ms ▼	G.729a 20ms ▼	G.711mu 20ms ▼	G.711A 20ms ▼
G.723 Silence Suppression:	<input type="radio"/> enable <input checked="" type="radio"/> disable				
Volume:	voice <input type="text" value="28"/>	input <input type="text" value="28"/>	DTMF <input type="text" value="23"/>		
Echo Cancelor:	<input checked="" type="radio"/> enable <input type="radio"/> disable				
Jitter Buffer:	Min. Delay <input type="text" value="90"/>		Max. Delay <input type="text" value="150"/>		
<input type="button" value="OK"/>					